Iccons BIS-HY420 Part B

Iccons

Chemwatch Hazard Alert Code: 2

Issue Date: 01/24/2017 Print Date: 01/27/2017 S.GHS.AUS.EN

Chemwatch: 74-2949 Version No: 2.1.1.1 Safety Data Sheet according to WHS and ADG requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Iccons BIS-HY420 Part B
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Adhesive mortar for fastening to concrete elements B-Component (Hardener).
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	Iccons
Address	12 Produce Drive Dandenong South VIC 3175 Australia
Telephone	+61 3 9706 4344
Fax	09 9768 3329
Website	www.iccons.com.au
Email	info@iccons.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	1800 039 008 (24hrs)
Other emergency telephone numbers	+61 3 9573 112

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
1800 039 008	1800 039 008	+612 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	S5
Classification [1]	Skin Sensitizer Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements



SIGNAL WORD WARNING

Hazard statement(s)

H317 May cause an allergic skin reaction.

Precautionary statement(s) Prevention

	•
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.

Page 2 of 7

Iccons BIS-HY420 Part B

Issue Date: 01/24/2017 Print Date: 01/27/2017

P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
94-36-0	1-<10	dibenzoyl peroxide
14808-60-7	1-<5	silica crystalline - quartz

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: ► Wash out immediately with water. ► If irritation continues, seek medical attention. ► Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If furnes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Foam.
- ► Dry chemical powder.
- ▶ BCF (where regulations permit).
- ► Carbon dioxide.

Special hazards arising from the substrate or mixture

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result Fire Incompatibility

Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	 ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon monoxide (CO) r carbon dioxide (CO2) nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.

Version No: 2.1.1.1

Iccons BIS-HY420 Part B

Issue Date: **01/24/2017** Print Date: **01/27/2017**

May emit poisonous fumes.
May emit corrosive fumes.

HAZCHEM Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

San cartion 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up.
Major Spills	Minor hazard. ► Clear area of personnel. ► Alert Fire Brigade and tell them location and nature of hazard. ► Control personal contact with the substance, by using protective equipment as required.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. 	
Storage incompatibility	► Avoid reaction with oxidising agents	

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	silica crystalline - quartz	Silica - Crystalline: Quartz (respirable dust) / Quartz (respirable dust)	0.1 mg/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
dibenzoyl peroxide	Benzoyl peroxide	15 mg/m3	1,200 mg/m3	7,000 mg/m3
silica crystalline - quartz	Silica, crystalline-quartz; (Silicon dioxide)	0.075 mg/m3	33 mg/m3	200 mg/m3


Ingredient	Original IDLH	Revised IDLH
dibenzoyl peroxide	7,000 mg/m3	1,500 mg/m3
silica crystalline - quartz	N.E. mg/m3 / N.E. ppm	50 mg/m3

Exposure controls

	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Appropriate engineering	The basic types of engineering controls are:
controls	Process controls which involve changing the way a job activity or process is done to reduce the risk.
	Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and
	"removes" air in the work environment.

Iccons BIS-HY420 Part B

Page 4 of 7 Issue Date: 01/24/2017 Print Date: 01/27/2017



Respiratory protection

Version No: 2.1.1.1

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS	-	AX-PAPR-AUS / Class 1
up to 50 x ES	-	AX-AUS / Class 1	-
up to 100 x ES	-	AX-2	AX-PAPR-2^

^{^ -} Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Black paste with characteristic odour; does not mix with water.		
Physical state	Non Slump Paste	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	116	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	ee section 7	
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 	
Possibility of hazardous reactions	See section 7	

Issue Date: 01/24/2017 Print Date: 01/27/2017

Iccons BIS-HY420 Part B

Conditions to avoid	s to avoid See section 7	See section 7	
Incompatible materials	e materials See section 7	See section 7	
Hazardous decomposition products	mposition See section 5	See section 5	

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological eff	octe

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.			
Ingestion	Ingestion of organic peroxides may produce nausea, vomiting, abnormal pain, stupor, bluish discoloration of skin and mucous membranes. Inflammation of the heart muscle may also occur.			
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. All organic peroxides are irritating to the skin and if allowed to remain on the skin, may produce inflammation; some are allergenic. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).			
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged or repeated skin contact with benzoyl peroxide may result in allergic skin reactions even at diluted concentrations. Ingestion results in abdominal pain, low body oxygen and severe depression. Chronic effects of exposure include allergic reactions characterised by redness, itching, oozing, crusting, and scaling of the skin and asthmatic wheezing. Although it does not exhibit complete carcinogenic or tumour-initiating activity, it has been associated with certain tumours of like papillomas and squamous cell carcinomas.			
	TOXICITY	IRRITATION		
Iccons BIS-HY420 Part B	Oral (Rat) LD50: >2000 mg/kg* ^[2]	Not Available		
	TOXICITY	IRRITATION		
dibenzoyl peroxide	dermal (mammal) LD50: >1000 mg/kg ^[2]	Eye (rabbit): 500 mg/24h - mild		
	Oral (rat) LD50: >950 mg/kg ^[1]	Skin effects (MAK): very weak		
cilios erustallino, quarta	TOXICITY	IRRITATION		
silica crystalline - quartz	Not Available	Not Available		
Legend:	Value obtained from Europe ECHA Registered Substances extracted from RTECS - Register of Toxic Effect of chemical S	Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data ubstances		
DIBENZOYL PEROXIDE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Benzoyl peroxide may cause double vision, breathing problems, excess saliva and tear formation, redness of the skin and changes in motor activity. It did not produce blood or biochemical adverse effects, gene mutation or evidence of cancer. Repeated oral administration may result in decreased weights of testes and the newborn. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity may be inadequate or limited in animal testing.			
SILICA CRYSTALLINE -	Evidence of carcinogenicity may be inadequate or limited in animal testing. WARNING: For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease. Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours.			

Aspiration Hazard Legend:

Carcinogenicity

Reproductivity

STOT - Single Exposure

STOT - Repeated Exposure

0

0

0

0 0

X − Data available but does not fill the criteria for classification
 ✓ − Data required to make classification available

Data Not Available to make classification

Acute Toxicity

Serious Eye

Mutagenicity

Damage/Irritation Respiratory or Skin sensitisation 0

0

0

Skin Irritation/Corrosion

Iccons BIS-HY420 Part B

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
dibenzoyl peroxide	LC50	96	Fish	0.0602mg/L	2
dibenzoyl peroxide	EC50	48	Crustacea	0.11mg/L	2
dibenzoyl peroxide	EC50	72	Algae or other aquatic plants	0.0422mg/L	2
dibenzoyl peroxide	EC50	72	Algae or other aquatic plants	0.0613mg/L	2
dibenzoyl peroxide	NOEC	72	Algae or other aquatic plants	0.02mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
dibenzoyl peroxide	LOW (Half-life = 14 days)	LOW (Half-life = 21.25 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
dibenzoyl peroxide	LOW (LogKOW = 3.46)

Mobility in soil

Ingredient	Mobility
dibenzoyl peroxide	LOW (KOC = 771)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- Fig container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

disposal

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

DIBENZOYL PEROXIDE(94-36-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Australia Hazardous Substances Information System - Consolidated Lists Monographs International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Australia Inventory of Chemical Substances (AICS) Passenger and Cargo Aircraft

SILICA CRYSTALLINE - QUARTZ(14808-60-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS) Australia Hazardous Substances Information System - Consolidated Lists International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

National Inventory

Chemwatch: 74-2949 Page 7 of 7 Issue Date: 01/24/2017 Version No: 2.1.1.1 Print Date: 01/27/2017

Iccons BIS-HY420 Part B

Australia - AICS	Y
Canada - DSL	Υ
Canada - NDSL	N (dibenzoyl peroxide; silica crystalline - quartz)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
silica crystalline - quartz	14808-60-7, 122304-48-7, 122304-49-8, 12425-26-2, 1317-79-9, 70594-95-5, 87347-84-0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.