**Iccons** Chemwatch: 5370-71 Chemwatch Hazard Alert Code: 2

Issue Date: 06/26/2023 Print Date: 06/25/2023 S.GHS.AUS.EN

Version No: 8.1 Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

Pro	duct	lden	tifier

Product name	BIS-PE GEN3, Comp. A
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains bisphenol A diglycidyl ether)
Chemical formula	Not Applicable
Other means of identification	Not Available

## Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Adhesive mortar for fastening to concrete elements A-Component (Resin). Use according to manufacturer's directions.

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Iccons	Sesto Fasteners Ltd
Address	383 Frankston Dandenong Road Dandenong South VIC 3175 Australia	5E Piermark Drive Albany Auckland 0632 New Zealand
Telephone	+61 3 9706 4344	+64 09 415 8564
Fax	Not Available	Not Available
Website	www.iccons.com.au	www.sestofasteners.co.nz
Email	info@iccons.com.au	info@sestofasteners.co.nz

## **Emergency telephone number**

Association / Organisation	Shore Care, Smales Farm	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	+64 09 486 7777 (24 hrs)	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

## **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

Poisons Schedule	S5
Classification [1]	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Carcinogenicity Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

## Label elements

Hazard pictogram(s)





Signal word Warning

nazard statement(s)		
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H351	Suspected of causing cancer.	

## Precautionary statement(s) Prevention

P201 Obtain special instructions before use. Chemwatch: **5370-71**Version No: **8.1** 

Page 2 of 9

**BIS-PE GEN3, Comp. A** 

Issue Date: **06/26/2023**Print Date: **06/25/2023** 

P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P261	Avoid breathing dust/fumes.	
P264	Wash all exposed external body areas thoroughly after handling.	

## Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P302+P352	IF ON SKIN: Wash with plenty of water.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	

## Precautionary statement(s) Storage

P405 Store locked up.

## Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
1675-54-3	30-<60	bisphenol A diglycidyl ether
16096-31-4	5-<15	1,6-hexanediol diglycidyl ether
Legend:	Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

#### **SECTION 4 First aid measures**

#### Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Wash out immediately with fresh running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Seek medical attention without delay; if pain persists or recurs seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>Urgent hospital treatment is likely to be needed.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Transport to hospital or doctor without delay.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 Firefighting measures**

## **Extinguishing media**

- ► Foam.
- ► Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.

Do not use water jets.

## Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Advice for firefighters

## Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- ▶ Prevent, by any means available, spillage from entering drains or water courses.

Version No: 8.1

## BIS-PE GEN3, Comp. A

Issue Date: **06/26/2023**Print Date: **06/25/2023** 

Fire/Explosion Hazard	Use water delivered as a fine spray to control fire and cool adjacent area.  Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO2) aldehydes other pyrolysis products typical of burning organic material.
HAZCHEM	27

## **SECTION 6 Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage.  Clean up all spills immediately.  Avoid contact with skin and eyes.  Wear impervious gloves and safety goggles.  Trowel up/scrape up.
Major Spills	<ul> <li>Environmental hazard - contain spillage.</li> <li>Minor hazard.</li> <li>Clear area of personnel.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Control personal contact with the substance, by using protective equipment as required.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 Handling and storage**

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>	
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>No smoking, naked lights or ignition sources.</li> <li>Store in a cool, dry, well-ventilated area.</li> </ul>	

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	<ul> <li>Avoid cross contamination between the two liquid parts of product (kit).</li> <li>If two part products are mixed or allowed to mix in proportions other than manufacturer's recommendation, polymerisation with gelation and evolution of heat (exotherm) may occur.</li> <li>This excess heat may generate toxic vapour</li> <li>Avoid reaction with amines, mercaptans, strong acids and oxidising agents strong alkalis</li> </ul>

## **SECTION 8 Exposure controls / personal protection**

## Control parameters

## Occupational Exposure Limits (OEL)

## INGREDIENT DATA

Not Available

## Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
bisphenol A diglycidyl ether	39 mg/m3	430 mg/m3	2,600 mg/m3
bisphenol A diglycidyl ether	90 mg/m3	990 mg/m3	5,900 mg/m3

Ingredient	Original IDLH	Revised IDLH
bisphenol A diglycidyl ether	Not Available	Not Available
1,6-hexanediol diglycidyl ether	Not Available	Not Available

# Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
------------	-----------------------------------	----------------------------------

Chemwatch: 5370-71 Version No: 8.1

BIS-PE GEN3, Comp. A

Page 4 of 9 Issue Date: 06/26/2023 Print Date: 06/25/2023

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
bisphenol A diglycidyl ether	E	≤ 0.1 ppm
1,6-hexanediol diglycidyl ether	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

#### **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Individual protection measures, such as personal protective equipment











#### Eye and face protection

Hands/feet protection

#### Safety glasses with side shields.

- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

#### Skin protection

#### See Hand protection below

#### NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

When handling liquid-grade epoxy resins wear chemically protective gloves , boots and aprons.

The performance, based on breakthrough times .of:

- · Ethyl Vinyl Alcohol (EVAL laminate) is generally excellent
- · Butyl Rubber ranges from excellent to good
- · Nitrile Butyl Rubber (NBR) from excellent to fair.
- · Neoprene from excellent to fair
- · Polyvinyl (PVC) from excellent to poor

As defined in ASTM F-739-96

- · Excellent breakthrough time > 480 min
- · Good breakthrough time > 20 min
- · Fair breakthrough time < 20 min · Poor glove material degradation
- Gloves should be tested against each resin system prior to making a selection of the most suitable type. Systems include both the resin and any hardener, individually and collectively)
- · DO NOT use cotton or leather (which absorb and concentrate the resin), natural rubber (latex), medical or polyethylene gloves (which absorb the resin)
- ► DO NOT use solvent to clean the skin

## **Body protection**

See Other protection below

#### Other protection

No special equipment needed when handling small quantities OTHERWISE:

#### Barrier cream

- Eyewash unit.

## Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A P1 Air-line*	-	A PAPR-P1
up to 50 x ES	Air-line**	A P2	A PAPR-P2
up to 100 x ES	-	A P3	-
		Air-line*	-
100+ x ES	-	Air-line**	A PAPR-P3

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

#### **SECTION 9 Physical and chemical properties**

Issue Date: **06/26/2023** Print Date: **06/25/2023** 

Appearance	Light beige coloured paste with characteristic odour; partly mixes with water.		
Physical state	Solid	Relative density (Water = 1)	1.45
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

Information	on	toxicological	effects
minorimation	011	toxicological	CITCOLS

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.  Inhalation hazard is increased at higher temperatures.		
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.		
Skin Contact	The material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.  The material may accentuate any pre-existing dermatitis condition Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.  Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Eye	There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.		
Chronic	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.  Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.  Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.  Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Based on experience with similar materials, there is a possibility that exposure to the material may reduce fertility in humans at levels which do not cause other toxic effects.		
	TOXICITY	IRRITATION	
BIS-PE GEN3, Comp. A	Not Available	Not Available	
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 2 mg/24h - SEVERE	
bisphenol A diglycidyl ether	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	
		Skin (rabbit): 500 mg - mild	

Skin: adverse effect observed (irritating)<sup>[1]</sup>

Version No: 8.1

# BIS-PE GEN3, Comp. A

Issue Date: 06/26/2023 Print Date: 06/25/2023

	1		
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg - moderate	
	Oral (Rat) LD50: 2900 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	
1,6-hexanediol diglycidyl ether		Skin (rabbit): slight *	
		Skin (rabbit):10 mg/24h - moderate	
		Skin: adverse effect observed (irritating) <sup>[1]</sup>	
Legend:	Value obtained from Europe ECHA Registered Substances - Acute specified data extracted from RTECS - Register of Toxic Effect of chel	toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise mical Substances	
BISPHENOL A DIGLYCIDYL ETHER	reproductive effects.  Cancer-causing potential: It has been concluded that bisphenol A digly in humans.  Genetic toxicity: Laboratory tests on genetic toxicity of BADGE have s Immunotoxicity: Animal testing suggests regular injections of diluted B Consumer exposure: Comsumer exposure to BADGE is almost exclus found any evidence of hormonal disruption.  Bisphenol A may have effects similar to female sex hormones and who damage male reproductive organs and sperm.  Glycidyl ethers can cause genetic damage and cancer. 55badger The substance is classified by IARC as Group 3:  NOT classifiable as to its carcinogenicity to humans.  Evidence of carcinogenicity may be inadequate or limited in animal testing the substance is classified by the substance or limited in animal testing.	OGE given over several months caused reduction in body weight but had no yoldyl ether cannot be classified with respect to its cancer-causing potential of far been negative.  ADGE may result in sensitization. Sively from migration of BADGE from can coatings into food. Testing has not en administered to pregnant women, may damage the foetus. It may also	
1,6-HEXANEDIOL DIGLYCIDYL ETHER	Hexion MSDS  Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.  The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.  The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
BISPHENOL A DIGLYCIDYL ETHER & 1,6-HEXANEDIOL DIGLYCIDYL ETHER	The following information refers to contact allergens as a group and may not be specific to this product.  Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.  Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) share many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative.  For 1,2-butylene oxide (ethyloxirane): In animal testing, ethyloxirane increased the incidence of tumours of the airways in animals exposed via inhalation. However, tumours were not observed in mice chronically exposed via skin. Two structurally related substances, oxirane (ethylene oxide) and methyloxirane (propylene oxide), which are also direct-acting alkylating agents, have been classified as causing cancer.		
	U		

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	<b>✓</b>	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

X − Data either not available or does not fill the criteria for classification
✓ − Data available to make classification

# **SECTION 12 Ecological information**

## Toxicity

DXICITY					
BIS-PE GEN3, Comp. A	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
bisphenol A diglycidyl ether	LC50	96h	Fish	1.2mg/l	2
	EC50	72h	Algae or other aquatic plants	9.4mg/l	2
	EC50	48h	Crustacea	1.1mg/l	2
	NOEC(ECx)	504h	Crustacea	0.3mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
1,6-hexanediol diglycidyl ether	LC50	96h	Fish	17-31mg/l	Not Available

Issue Date: 06/26/2023 Print Date: 06/25/2023

	EC50	48h	Crustacea	47mg/l	Not Available
	EC50(ECx)	48h	Crustacea	47mg/l	Not Available
Legend:	Ecotox databas		ed Substances - Ecotoxicological Information - Aqu ard Assessment Data 6. NITE (Japan) - Bioconcent		

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. DO NOT discharge into sewer or waterways

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
bisphenol A diglycidyl ether	HIGH	HIGH

#### Bioaccumulative potential

Ingredient	Bioaccumulation
bisphenol A diglycidyl ether	MEDIUM (LogKOW = 3.8446)

## Mobility in soil

Ingredient	Mobility
bisphenol A diglycidyl ether	LOW (KOC = 1767)

## **SECTION 13 Disposal considerations**

#### Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

#### Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product. Waste Management

Product / Packaging disposal

Production waste from epoxy resins and resin systems should be treated as hazardous waste in accordance with National regulations. Fire retarded resins containing halogenated compounds should also be treated as special waste. Accidental spillage of resins, curing agents and their formulations should be contained and absorbed by special mineral absorbents to prevent them from entering the environment. Contaminated or surplus product should not be washed down the sink, but preferably be fully reacted to form cross-linked solids which is

non-hazardous and can be more easily disposed.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Material may be disposed of by controlled burning in an approved incinerator or buried in an approved landfill.
- Prior to disposal in a landfill the material should be mixed with the other component and reacted to render the material inert.

## **SECTION 14 Transport information**

#### Labels Required



Marine Pollutant	NO
HAZCHEM	2Z

#### Land transport (ADG)

UN number or ID number	3077		
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains bisphenol A diglycidyl ether)		
Transport hazard class(es)	Class 9 Subsidiary risk Not Applicable		
Packing group	III		
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions 274 331 335 375 AU01  Limited quantity 5 kg		

Issue Date: **06/26/2023**Print Date: **06/25/2023** 

are not subject to this Code when transported by road or rail in;

- (a) packagings;
- (b) IBCs; or
- (c) any other receptacle not exceeding 500 kg(L).
- Australian Special Provisions (SP AU01) ADG Code 7th Ed.

#### Air transport (ICAO-IATA / DGR)

UN number	3077			
UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (contains bisphenol A diglycidyl ether)			
	ICAO/IATA Class	9		
Transport hazard class(es)	ICAO / IATA Subrisk	Not Applicable		
	ERG Code	9L		
	ENO COGO	32		
Packing group	III			
Environmental hazard	Not Applicable			
	Special provisions		A97 A158 A179 A197 A215	
	Cargo Only Packing Instructions		956	
	Cargo Only Maximum Qty / Pack		400 kg	
Special precautions for user	Passenger and Cargo	Packing Instructions	956	
	Passenger and Cargo	Passenger and Cargo Maximum Qty / Pack		
	Passenger and Cargo	Limited Quantity Packing Instructions	Y956	
	Passenger and Cargo	Limited Maximum Qty / Pack	30 kg G	

#### Sea transport (IMDG-Code / GGVSee)

UN number	3077			
UN proper shipping name	ENVIRONMENTALLY	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains bisphenol A diglycidyl ether)		
Transport hazard class(es)	IMDG Class  IMDG Subrisk	Not Applicable		
Packing group	III			
Environmental hazard	Not Applicable			
Special precautions for user	EMS Number Special provisions Limited Quantities	F-A, S-F 274 335 966 967 969 5 kg		

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
bisphenol A diglycidyl ether	Not Available
1,6-hexanediol diglycidyl ether	Not Available

## Transport in bulk in accordance with the IGC Code

•	
Product name	Ship Type
bisphenol A diglycidyl ether	Not Available
1,6-hexanediol diglycidyl ether	Not Available

## **SECTION 15 Regulatory information**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## bisphenol A diglycidyl ether is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### 1,6-hexanediol diglycidyl ether is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

## Chemical Footprint Project - Chemicals of High Concern List

# National Inventory Status

=	
National Inventory	Statu

Version No: 8.1

#### BIS-PE GEN3, Comp. A

Issue Date: 06/26/2023 Print Date: 06/25/2023

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (bisphenol A diglycidyl ether; 1,6-hexanediol diglycidyl ether)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (bisphenol A diglycidyl ether; 1,6-hexanediol diglycidyl ether)	
Vietnam - NCI	Yes	
Russia - FBEPH	No (1,6-hexanediol diglycidyl ether)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

#### **SECTION 16 Other information**

Revision Date	06/26/2023
Initial Date	09/25/2019

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
7.1	03/10/2023	Classification change due to full database hazard calculation/update.
8.1	06/26/2023	Physical and chemical properties - Appearance, Exposure controls / personal protection - Personal Protection (other), Identification of the substance / mixture and of the company / undertaking - Use

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### **Definitions and abbreviations**

PC - TWA: Permissible Concentration-Time Weighted Average

PC - STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit₀

IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.