FoamFlo Fire

Iccons

Chemwatch Hazard Alert Code: 4

Chemwatch: 5417-75 Issue Date: 12/23/2022 Version No: 3.1 Print Date: 03/23/2023 Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	FoamFlo Fire
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Foam. Relevant identified uses

Details of the manufacturer or supplier of the safety data sheet

Registered company name	ccons		
Address	3 Frankston Dandenong Road Dandenong South VIC 3175 Australia		
Telephone	+61 3 9706 4344		
Fax	Not Available		
Website	www.iccons.com.au		
Email	info@iccons.com.au		

Emergency telephone number

o , 1		
Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	
Emergency telephone numbers	+61 1800 951 288	
Other emergency telephone numbers	+61 3 9573 3188	

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	S6
Classification ^[1]	Aerosols Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Sensitisation (Respiratory) Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Carcinogenicity Category 2, Reproductive Toxicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

AUH044	Risk of explosion if heated under confinement.	
H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	

FoamFlo Fire

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s) Prevention

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

Precautionary statement(s) Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P308+P313	P308+P313 IF exposed or concerned: Get medical advice/ attention.	
P342+P311	I2+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.	
P302+P352	IF ON SKIN: Wash with plenty of water.	

Precautionary statement(s) Storage

P405	Store locked up.	
P410+P412	tect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9016-87-9	30-<60	MDI oligomer
1244733-77-4	10-<30	tris(2-chloroisopropyl)phosphate
86675-46-9	10-<30	halogenated polyether polyols
78-40-0	<10	triethyl phosphate
115-10-6	<10	dimethyl ether
68476-85-7.	<20	hydrocarbon propellant
Legend:	I: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If aerosols come in contact with the eyes: Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	 Following uptake by inhalation, move person to an area free from risk of further exposure. Oxygen or artificial respiration should be administered as needed. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic. A physician should be consulted. If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

All persons handling organic phosphorus ester materials regularly should undergo regular medical examination with special stress on the central nervous systems. Whilst atropine or pyridine-2-aldoxime methiodide (PAM) are beneficial antidotes for acute phosphate ester poisonings, they are of little value in reversing acute or chronic neurological damage due to phosphites and some types of aryl phosphate.

For sub-chronic and chronic exposures to isocyanates:

- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.
- Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates.
- ۶ Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

SECTION 5 Firefighting measures

Extinguishing media

- Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.
- Presents additional hazard when fire fighting in a confined space.
- Cooling with flooding guantities of water reduces this risk
- Water spray or fog may cause frothing and should be used in large quantities.

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the	he substrate or mixture
Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Combustion products include: carbon dioxide (CO2) isocyanates and minor amounts of hydrogen cyanide hydrogen chloride phosgene nitrogen oxides (NOx) phosphorus oxides (POx) other pyrolysis products typical of burning organic material.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear protective clothing, impervious gloves and safety glasses.
- Shut off all possible sources of ignition and increase ventilation.

Page 4 of 13

FoamFlo Fire

Major Spills	 Avoid contamination with water, alkalies and detergent solutions. Material reacts with water and generates gas, pressurises containers with even drum rupture resulting. DO NOT reseal container if contamination is suspected. Open all containers with care. DO NOT touch the spill material Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves.
--------------	--

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Consider storage under inert gas. Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can Store in original containers in approved flammable liquid storage area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	 Aerosol dispenser. Check that containers are clearly labelled.
Storage incompatibility	 Avoid reaction with water, alcohols and detergent solutions. Isocyanates are electrophiles, and as such they are reactive toward a variety of nucleophiles including alcohols, amines, and even water. Upon treatment with an alcohol, an isocyanate forms a urethane linkage. If a di-isocyanate is treated with a compound containing two or more hydroxyl groups, such as a diol or a polyol, polymer chains are formed, which are known as polyurethanes. Avoid reaction with oxidising agents Avoid strong acids, bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	MDI oligomer	Isocyanates, all (as-NCO)	0.02 mg/m3	0.07 mg/m3	Not Available	Not Available
Australia Exposure Standards	dimethyl ether	Dimethyl ether	400 ppm / 760 mg/m3	950 mg/m3 / 500 ppm	Not Available	Not Available
Australia Exposure Standards	hydrocarbon propellant	LPG (liquified petroleum gas)	1000 ppm / 1800 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3
MDI oligomer	0.15 mg/m3 3.6 mg/m3			22 mg/m3
triethyl phosphate	23 mg/m3	250 mg/m3		320 mg/m3
dimethyl ether	3,000 ppm	3800* ppm		7200* ppm
hydrocarbon propellant	65,000 ppm	2.30E+05 ppm		4.00E+05 ppm
Ingredient	Original IDLH		Revised IDLH	
MDI oligomer	Not Available		Not Available	
tris(2-chloroisopropyl)phosphate	Not Available		Not Available	
halogenated polyether polyols	Not Available		Not Available	
triethyl phosphate	Not Available		Not Available	
dimethyl ether	Not Available		Not Available	
hydrocarbon propellant	2,000 ppm		Not Available	
Occupational Exposure Banding				

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
tris(2-chloroisopropyl)phosphate	E	≤ 0.1 ppm	
halogenated polyether polyols	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the		

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. Page 5 of 13

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
triethyl phosphate	E ≤ 0.1 ppm			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.			
xposure controls				
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.			
Individual protection measures, such as personal protective equipment				
Eye and face protection	No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: Safety glasses with side shields. NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.			
Skin protection	See Hand protection below			
Hands/feet protection	 NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Isocyanate resistant materials include Teflon, Viton, nitrile rubber and some PVA gloves. Protective gloves and overalls should be worn as specified in the appropriate national standard. Contaminated garments should be removed promptly and should not be re-used until they have been decontaminated. NOTE: Natural rubber, neoprene, PVC can be affected by isocyanates No special equipment needed when handling small quantities. OTHERWISE: For potentially moderate exposures: Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: Wear chemical protective gloves, eg. PVC. and safety footwear. 			
Body protection	See Other protection below			
Other protection	No special equipment needed when handling small quantities. OTHERWISE: Vorralls. Skin cleansing cream. Eyewash unit.			

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

FoamFlo Fire

Material	CPI
BUTYL	A
NEOPRENE	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P2	-	AX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AX-AUS / Class 1 P2	-
up to 100 x ES	-	AX-2 P2	AX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask

smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance			
Physical state	Liquid	Relative density (Water = 1)	1.05 @20C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	*460 (propellant)
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	*-12 (propellant)	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	*-83 (propellant)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	<300 @50C	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7	
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur. Presence of elevated temperatures. 	
Possibility of hazardous reactions	e section 7	
Conditions to avoid	pe section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranoia. Gastrointestinal disturbances are characterised by nausea and vomiting. Pulmonary sensitisation may produce asthmatic reactions ranging from minor breathing difficulties to severe allergic attacks; this may occur following a single acute exposure or may develop without warning for several hours after exposure. WARNING :Intentional misuse by concentrating/inhaling contents may be lethal. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure. Not considered to be a risk because of the extreme volatility of the gas.
Chronic	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

tris(2- chloroisopropyl)phosphate
MDI oligomer
FoamFlo Fire

halogenated polyether polyols	Oral (Rat) LD50: 917 mg/kg ^[2]	Eye (rabbit) : Mild *	
		Skin (rabbit): Not irritating *	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >20000 mg/kg ^[1]	Eye : Severe *	
triethyl phosphate	Inhalation(Rat) LC50: >8.817 mg/L4h ^[1]	Eye: adverse effect observed (irritating) ^[1]	
	Oral (Rat) LD50: 1165 mg/kg ^[2]	Skin : Severe *	
		Skin: no adverse effect observed (not irritating) ^[1]	
	τοχιςιτγ	IRRITATION	
dimethyl ether	Inhalation(Rat) LC50: >20000 ppm4h ^[1]	Not Available	
	τοχιςιτγ	IRRITATION	
hydrocarbon propellant	Inhalation(Rat) LC50: 658 mg/l4h ^[2]	Not Available	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		

of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.		
Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly.	MDI OLIGOMER	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing,

Mutagenicity

×

Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more

		effect. Of the several members of diisocyanates test others produced a harmless outcome. This group of The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans Evidence of carcinogenicity may be inadequate or I	hay aggravate symptoms. Allergy ca terised by increased susceptibility to by allergen specific immune-comple he delayed type with onset up to four can cause their inflammation, with em symptoms that may occur includ rway toxicity and skin sensitization. I sted on experimental animals by inh of compounds has therefore been cla s. limited in animal testing.	using activity is due to interactions with proteins. o nasal inflammation, asthma and eczema. exes of the IgG type; cell-mediated reactions (T r hours following exposure. wheezing, gasping, severe distress, even loss of le headache, sleep disturbance, euphoria, Monomers and prepolymers exhibit similar respiratory alation and oral exposure, some caused cancer while	
TRIS(CHLOROISOPROPYL)PHOSPHAT		ingredient in rubber or plastic to the outer surface a known to bloom from car interior plastics, TVs and These substances are absorbed to various organs, For tris(2-chloro-1-methylethyl)phosphate (TCPP) The flame retardant product supplied in the EU, ma	after curing. Blooming is quickened b computer monitors. particularly the liver and kidney but arketed as TCPP, is actually a reaction	also the brain.	
HALOGENATED POLYETHE POLYOI		* Solvay SDS From available experimental data, the potential for polybrominated fire retardants (PBFRs) to cause cancer, hormonal dysfunction and neuro-developmental toxicity are of concern. Their structural similarities to the polychlorinated diphenyl ethers, pitrofen and polychlorin			
	biphenyls add to concerns for their health effects. I hey cause mild eye, airway and skin irritation, damage to the liver, thyroid and se		effect of TEP is not assumed. The substance is inhibition of cholinesterase) without indicating delayed showed no irritation properties. The most ate irritation in 1 of 3 animals. According to the e administered orally or i.p. to rodents is eliminated indicates a markedly lower adsorption than with oral jain, elevated liver and adrenals weight were he available data is about 670 mg/kg bw). A subacute termined a NOEL of 100 mg/kg bw (increased liver a NOAEL of 1000 mg/kg bw was derived. After high cholineesterases are described. In mice, a NOAEL of i). In rats a NOEL following inhalatory exposure (5h/d oral doses up to 6700 mg/kg bw. The NOAEL in the ing a small number of animals the litter size was hn o symptoms of poisoning in the parent animals 335 mg/kg bw/day. Neither testicular weights nor the dose 6700 mg/kg bw/day). A more recent 28-day Bayer 1992]. A teratogenicity study in rats showed no developmental toxicity). In the highest dose there al toxicity (NOEL 125 mg/kg bw/day). Genetic Toxicity utations without metabolic activation in S. e endpoint gene mutation a HPRT test in V79 cell vation. In an in vitro UDS test on rat hepatocytes logaster in the limited documented recessive-lethal arrow, dominant lethal test) were negative. ible effects and mutations in humans. single-dose studies. Animal testing showed that the mal testing suggests that the lighter the species, the others were irritating but not sensitizing. Again, the did not cause toxicity to the embryo or the foetus, and n. Repeated or prolonged exposure to irritants may o a family of chemicals producing damage or change		
HYDROCARBON PROPELLAN		No significant acute toxicological data identified in literature search. inhalation of the gas			
MDI OLIGOMER & TRIETHY PHOSPHAT		The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.			
TRIS CHLOROISOPROPYL)PHOSPHAT & TRIETHYL PHOSPHAT	(2- ГЕ	Alkyl esters of phosphoric acid exhibit a low to mod	-	d. From studies done on mice, they are not likely to n effect on newborn rats at high doses to the pregnant	
Acute Toxicity	~		Carcinogenicity	✓	
Skin Irritation/Corrosion	~		Reproductivity	×	
Serious Eye Damage/Irritation	~		STOT - Single Exposure	×	
Respiratory or Skin sensitisation	~		STOT - Repeated Exposure	~	
	~		Assistion Honord	V	

Aspiration Hazard

×

Chemwatch: 5417-75 Version No: 3.1

Legena:

SECTION 12 Ecological information

	Endpoint	Test Duration (hr)	Species	Value	Source
FoamFlo Fire	Not Available	Not Available	Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Source
MDI oligomer	Not Available	Not Available	Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	65335mg/l	1
	EC50	96h	Algae or other aquatic plants	4mg/l	1
	EC50(ECx)	96h	Algae or other aquatic plants	4mg/l	1
tris(2-	ErC50	72h	Algae or other aquatic plants	4mg/l	1
chloroisopropyl)phosphate	BCF	1008h	Fish	0.8-2.8	7
	LC50	96h	Fish	56.2mg/l	Not Availabl
	EC50	72h	Algae or other aquatic plants	82mg/l	Not Availabl
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	500mg/l	Not Availabl
	EC50	96h	Algae or other aquatic plants	>1000mg/l	2
alogenated polyether polyols	EC50	72h	Algae or other aquatic plants	>1000mg/l	Not Availab
	LC50	96h	Fish	>1000mg/l	Not Availab
	EC50	48h	Crustacea	>1000mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	0.5-0.8	7
triethyl phosphate	NOEC(ECx)	Not Available	Crustacea	31.6mg/l	Not Availab
	EC50	72h	Algae or other aquatic plants	900mg/l	Not Availab
	LC50	96h	Fish	>100mg/l	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	LC50	96h	Fish	1783.04mg/l	2
dimethyl ether	EC50	48h	Crustacea	>4400mg/L	2
	NOEC(ECx)	48h	Crustacea	>4000mg/l	1
	EC50	96h	Algae or other aquatic plants	154.917mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Sourc
hudrooorber mensellent	EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
hydrocarbon propellant	LC50	96h	Fish	24.11mg/l	2
	EC50	96h	Algae or other aquatic plants	7.71mg/l	2
Legend:			HA Registered Substances - Ecotoxicological Informati Aquatic Hazard Assessment Data 6. NITE (Japan) - Bic		

Harmful to aquatic organisms.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
tris(2-chloroisopropyl)phosphate	HIGH	HIGH
triethyl phosphate	HIGH	HIGH
dimethyl ether	LOW	LOW

Continued...

Bioaccumulative potential

dimethyl ether

Ingredient	Bioaccumulation
tris(2-chloroisopropyl)phosphate	LOW (BCF = 4.6)
triethyl phosphate	LOW (BCF = 1.3)
dimethyl ether	LOW (LogKOW = 0.1)
Mobility in soil	
Ingredient	Mobility
tris(2-chloroisopropyl)phosphate	LOW (KOC = 1278)
triethyl phosphate	LOW (KOC = 47.96)

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans. Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product.

SECTION 14 Transport information

Labels Required



HIGH (KOC = 1.292)

 Marine Pollutant
 NO

 HAZCHEM
 Not Applicable

Land transport (ADG)

i 、 ,				
UN number or ID number	1950			
UN proper shipping name	AEROSOLS			
Transport hazard class(es)	Class 2.1 Subsidiary risk Not Applicable			
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions63 190 277 327 344 381Limited quantity1000ml			

Air transport (ICAO-IATA / DGR)

UN number	1950				
UN proper shipping name	Aerosols, flammable				
Transport hazard class(es)	ICAO/IATA Class	2.1 Not Applicable			
	ERG Code	10L			
Packing group	Not Applicable				
Environmental hazard	Not Applicable	Not Applicable			
	Special provisions		A145 A167 A802		
Special precautions for user	Cargo Only Packing Instructions		203		
	Cargo Only Maximum Qty / Pack		150 kg		

FoamFlo Fire

Passenger and Cargo Packing Instructions	203
Passenger and Cargo Maximum Qty / Pack	75 kg
Passenger and Cargo Limited Quantity Packing Instructions	Y203
Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	1950	
UN proper shipping name	AEROSOLS	
Transport hazard class(es)	IMDG Class 2.1 IMDG Subrisk Not Applicable	
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number Special provisions Limited Quantities	F-D, S-U 63 190 277 327 344 381 959 1000 ml

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
MDI oligomer	Not Available
tris(2-chloroisopropyl)phosphate	Not Available
halogenated polyether polyols	Not Available
triethyl phosphate	Not Available
dimethyl ether	Not Available
hydrocarbon propellant	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
MDI oligomer	Not Available
tris(2-chloroisopropyl)phosphate	Not Available
halogenated polyether polyols	Not Available
triethyl phosphate	Not Available
dimethyl ether	Not Available
hydrocarbon propellant	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

	MDI oligomer is found on the following regulatory lists	
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
	Australia Model Work Health and Safety Regulations - Hazardous chemicals (other than lead) requiring health monitoring	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	
l	tris(2-chloroisopropyl)phosphate is found on the following regulatory lists	
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
ļ	halogenated polyether polyols is found on the following regulatory lists	
	Not Applicable	
	triethyl phosphate is found on the following regulatory lists	
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	
l	dimethyl ether is found on the following regulatory lists	
	Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
	Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	
l	hydrocarbon propellant is found on the following regulatory lists	

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC) Chemical Footprint Project - Chemicals of High Concern List

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	No (halogenated polyether polyols)	
Canada - DSL	No (halogenated polyether polyols)	
Canada - NDSL	No (MDI oligomer; tris(2-chloroisopropyl)phosphate; halogenated polyether polyols; triethyl phosphate; dimethyl ether; hydrocarbon propellant)	
China - IECSC	No (halogenated polyether polyols)	
Europe - EINEC / ELINCS / NLP	No (MDI oligomer; halogenated polyether polyols)	
Japan - ENCS	No (halogenated polyether polyols)	
Korea - KECI	No (halogenated polyether polyols)	
New Zealand - NZIoC	No (halogenated polyether polyols)	
Philippines - PICCS	No (halogenated polyether polyols)	
USA - TSCA	No (halogenated polyether polyols)	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (halogenated polyether polyols; triethyl phosphate)	
Vietnam - NCI	Yes	
Russia - FBEPH	No (halogenated polyether polyols)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	12/23/2022
Initial Date	07/23/2020

SDS Version Summary

Version	Date of Update	Sections Updated
3.1	12/23/2022	Classification review due to GHS Revision change.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

Page 13 of 13

FoamFlo Fire

TEL (+61 3) 9572 4700.