

TDS | 2042.1

KITCHEN & BATHROOM SILICONE SEALANT





KITCHEN & BATHROOM SILICONE SEALANT

ICCONS® Kitchen & Bathroom Silicone is a premium, neutral-cure, white sanitary silicone sealant. Its neutral-cure formula is low odour, anti-fungal & mould resistant. It provides long-term UV stability & remains permanently elastic to accommodate joint movement. Ideal for kitchens & bathrooms, this silicone offers excellent adhesion to most surfaces.

FEATURES

- ✓ Sanitary Grade
- ✓ Mould Resistant
- ✓ Neutral Cure
- ✓ Non-corrosive
- ✓ Highly Flexible



TYPICAL APPLICATIONS

- Kitchens
- Bathrooms
- Bathtubs
- Shower bases
- Shower screens
- Toilets
- Sinks
- Vanities
- Plumbing fixtures
- Air-conditioning systems

SUBSTRATE

Suitable for most building substrates:

- Galvanised iron & steel
- Glazed & ceramic tiles
- Sheet metal
- Aluminium
- Glass
- Good adhesion with various porous materials
- Timber
- Concrete

ADVANTAGES

- Rapid curing
- Highly flexible
- Waterproof
- UV-resistant
- Neutral curing
- Low odour
- Permanently elastic
- Excellent adhesion
- Non-slumping

PRODUCT CHARACTERISTICS

COLOUR	Translucent, White
APPEARANCE	Fine, uniform paste
CURING METHOD	Neutral cure
SERVICE TEMPERATURE	-30°C to +200°C
PRODUCT CODE	Translucent: FSA-STP300-KB White: FSA-SWP300-KB
CARTRIDGE SIZE	300mL

Part No.	Description	Colour	 Qty.	 Qty.
FSA-STP300-KB	300ml Kitchen & Bathroom Silicone Sealant	Translucent	12	1536
FSA-SWP300-KB	300ml Kitchen & Bathroom Silicone Sealant	White	12	1536



TYPICAL PROPERTIES

ITEMS	C*a/T*b/S*c/O*d	UNIT	REQUIREMENT
Appearance		/	Fine, uniform paste
Density		g/cm ³	1.00±0.10
Sagging		mm	≤1
Tack free	///Finger	min	≤15
Hardness, Shore A	7d///	/	15~30
Curing depth	24h///	mm	≥2.5
	7d///	mm	≥6.0
Elongation at break	7d///	%	≥500
Tensile Strength	7d///	MPa	≥0.6

NOTES:

*a: Conditioning, specimen is conditioned under (23±2)°C, (50±5)% relative humidity if not specified;

*b: Testing Condition, specimen is tested at (23±2) °C, (50±5)% relative humidity if not specified;

*c: Substrate

*d: Others need to be specified.

DIRECTIONS FOR USE

APPLICATION TEMPERATURE: +5°C to +45°C

Use only in well-ventilated areas. May cause an allergic skin reaction.

1. Prepare the surface by ensuring it is clean, dry, & free from dust or contaminants.
2. Cut the nozzle at a 45° angle & insert the cartridge into a caulking gun.
3. Hold the gun at a 45° angle & apply an even bead of sealant.
4. Tool & smooth the sealant before it begins to skin.

Note: Skin formation occurs within 5-10 minutes. Full cure of 6mm depth is reached in approximately 7 days. Uncured product may be cleaned using a suitable solvent.

RESTRICTIONS FOR USE

- Do not apply to substrates where the surface temperature exceeds +50°C or when the ambient temperature is below 5°C.
- Do not apply to surfaces that come into direct contact with food.
- Do not use for structural glazing applications.
- Do not apply to any surfaces that bleed oil, plasticizers, or solvents—such as oil-soaked wood, oil-based crack fillers, or certain uncured or sulfur-cured materials—or to wet surfaces.

SAFETY DIRECTIONS

Keep out of reach of children. Before operation, please carefully read the specifications of products and material, and instructions on the package of container. For more information about safety, please refer to the SDS.

SHELF LIFE

12 months when stored in original, unopened packaging. Keep out of direct sunlight & store in cool, well-ventilated environment between +5°C to +25°C.

DISCLAIMER

The details provided in this Technical Data Sheet (TDS) are based on ICCONS' knowledge at the time of publication. No warranty is given regarding specific product characteristics, and this document shall not be interpreted as forming a legally enforceable contract. It is supplied for guidance only concerning product selection, safe handling, application, storage, transportation, and disposal.



NOTES

ICCONS® PTY LTD

VICTORIA - Head Office

383 Frankston Dandenong Rd,
Dandenong South,
Victoria, 3175
P: **03 9706 4344**

NSW Branch

Unit A, 17 Seddon Street,
Bankstown,
New South Wales, 2200
P: **02 9791 6869**

OLD Branch

42-44 Nealdon Dr,
Meadowbrook,
Queensland, 4131
P: 07 3200 6455

FNQ Branch

41 Corporate Crescent,
Garbutt,
Queensland, 4814
P: **07 2111 3453**

S.A Branch

29-31 Weaver Street,
Edwardstown,
South Australia, 5039
P: **08 8234 5535**

W.A. Branch

Unit 4, 79 Gnangara Rd,
Wangara, WA 6065
saleswa@iccons.com.au
P: **08 6305 0008**

N.T Branch

Unit 1, 14 Menmuir Street,
Winnellie,
Northern Territory, 0820
P: **08 8947 2758**

NEW ZEALAND

SESTO FASTENERS

5E Piermark Drive,
Rosedale, Auckland,
New Zealand, 0632
P: **+64 9415 8564**
E: **sestofasteners@gmail.com**

THAILAND

ICCONS® (Thailand) Co. Ltd.

55 Phetkasem 62/3,
Bangkhuae, Bangkok
Thailand, 0160
P: + 66 2 801 0764
F: + 66 2 801 0764
M: + 66 8 1 710 8745
E: icconsthailand@iccons.com.au